

FAG 22338-K-MB + AH2338G参数

尺寸	d_{1H}	180	mm	-
	D	400	mm	-
	B	132	mm	-
	a	7	mm	-
	b	26	mm	-
	D_1	338.2	mm	-
	$D_{a \max}$	380	mm	-
	l	160	mm	-
	n_s	23.5	mm	-
	$r_{a \max}$	4	mm	-
	r_{\min}	5	mm	-
	说明		AH2338G	
重量	m	77300	g	质量
	m_1	6020	g	质量, 退卸套
基本额定载荷	C_r	1860000	N	基本额定动载荷, 径向
计算系数	e	0.37		-
	Y_1	1.83		-
	Y_2	2.72		-
基本额定载荷	C_{0r}	2500000	N	基本额定静载荷, 径向
计算系数	Y_0	1.79		-
极限转速	n_G	2010	r/min	极限转速
参考转速	n_B	1220	r/min	参考速度
疲劳极限载荷	C_{ur}	213000	N	疲劳极限载荷, 径向
尺寸	d	190	mm	-
	d_{2G}	M200x3		-
	$d_{a \min}$	210	mm	-
	d_s	12.5	mm	-

FAG 22338-K-MB + AH2338G图片



参考资料:<http://www.sozhou.com/p/00adaddf.html>