

## FAG 32919参数

参考转速	$n_B$	2900	r/min	参考速度	
说明		T2BC095		根据 DIN ISO 355 的 对应型号	
尺寸	$d$	95	mm	-	
	$D$	130	mm	-	
	$T$	23	mm	-	
	$a$	23	mm	-	
	$B$	23	mm	-	
	$C$	18	mm	-	
	$C_{a \text{ min}}$	5	mm	-	
	$C_{b \text{ min}}$	5	mm	-	
	$D_{a \text{ max}}$	123	mm	-	
	$D_{a \text{ min}}$	121	mm	-	
	$D_{b \text{ min}}$	125	mm	-	
	$d_1$	113	mm	-	
	$d_{a \text{ max}}$	102	mm	-	
	$d_{b \text{ min}}$	102	mm	-	
	$r_{1, 2 \text{ min}}$	1.5	mm	-	
	$r_{3, 4 \text{ min}}$	1.5	mm	-	
	$r_{a \text{ max}}$	1.5	mm	-	
	$r_{b \text{ max}}$	1.5	mm	-	
	基本额定载荷	$C_r$	102000	N	基本额定动载荷，径向
		$C_{0r}$	181000	N	基本额定静载荷，径向
计算系数	$e$	0.36		-	
	$Y$	1.68		-	
	$Y_0$	0.92		-	
疲劳极限载荷	$C_{ur}$	22000	N	疲劳极限载荷，径向	
极限转速	$n_G$	5300	r/min	极限转速	

FAG 32919图片

