

FAG 31316参数

计算系数	Y	0.73		-
	Y_0	0.4		-
疲劳极限载荷	C_{ur}	30500	N	疲劳极限载荷，径向
极限转速	n_G	4150	r/min	极限转速
参考转速	n_B	3100	r/min	参考速度
说明		T7GB080		根据 DIN ISO 355 的 对应型号
尺寸	$C_{b \min}$	15.5	mm	-
	$D_{a \max}$	158	mm	-
	$D_{a \min}$	134	mm	-
	$D_{b \min}$	159	mm	-
	d_1	122.4	mm	-
	$d_{a \max}$	97	mm	-
	$d_{b \min}$	92	mm	-
	$r_{1, 2 \min}$	3	mm	-
	$r_{3, 4 \min}$	2.5	mm	-
	$r_{a \max}$	3	mm	-
	$r_{b \max}$	2.5	mm	-
重量	m	4160	g	质量
基本额定载荷	C_r	227000	N	基本额定动载荷，径向
	C_{0r}	270000	N	基本额定静载荷，径向
计算系数	e	0.83		-
尺寸	d	80	mm	-
	D	170	mm	-
	T	42.5	mm	-
	a	53	mm	-
	B	39	mm	-
	C	27	mm	-

FAG 31316图片

