


FAG NJ2210-E-TVP2 + HJ210-E参数

尺寸	D_1	78.3	mm	-
	$D_{a\ max}$	83	mm	-
	d_1	64	mm	-
	$d_{a\ max}$	58	mm	-
	$d_{a\ min}$	57	mm	-
	$d_{c\ min}$	67	mm	-
	E	81.5	mm	-
	F	59.5	mm	-
	$r_{l\ min}$	1.1	mm	-
	$r_{a\ max}$	1	mm	-
	$r_{al\ max}$	1	mm	-
	r_{min}	1.1	mm	-
	s	1.3	mm	距离中心位置的轴向偏移
说明		HJ210-E		型号, L 型圈
重量	m	586	g	质量
	m_1	60	g	质量, L 型圈
基本额定载荷	C_r	92000	N	基本额定动载荷, 径向
	C_{0r}	88000	N	基本额定静载荷, 径向
极限转速	n_G	9700	r/min	极限转速
参考转速	n_B	5400	r/min	参考速度
尺寸	d	50	mm	-
	D	90	mm	-
	B	23	mm	-
	B_1	5	mm	-
	B_2	9	mm	-
疲劳极限载荷	C_{ur}	15000	N	疲劳极限载荷, 径向

FAG NJ2210-E-TVP2 + HJ210-E图片



参考资料:<http://www.sozhou.com/p/0a565a52.html>

