

### INA GIKPSR12-PS参数

|        |                     |               |    |   |
|--------|---------------------|---------------|----|---|
| 尺寸     | d                   | 12            | mm | 轴承座孔径公差：H7<br>(算术平均值) 公差：<br>+0,018 / 0 |
|        | d <sub>2 max</sub>  | 33            | mm | -                                       |
|        | l <sub>4</sub>      | 66.5          | mm | -                                       |
| 说明     |                     | 0.005 - 0.045 | mm | 径向内部游隙                                  |
| 尺寸     | B                   | 16            | mm | 公差：0 / -0,12                            |
|        | C <sub>1</sub>      | 12            | mm | -                                       |
|        | D                   | 26            | mm | -                                       |
|        | d <sub>1</sub>      | 15.4          | mm | -                                       |
|        | d <sub>3</sub>      | M12x1.25      |    | -                                       |
|        | d <sub>4</sub>      | 17.5          | mm | -                                       |
|        | d <sub>5</sub>      | 22            | mm | -                                       |
|        | d <sub>K</sub>      | 22.2          | mm | -                                       |
|        | h <sub>1</sub>      | 50            | mm | -                                       |
|        | l <sub>3 min</sub>  | 18            | mm | -                                       |
|        | l <sub>5</sub>      | 6.5           | mm | -                                       |
|        | l <sub>7 min</sub>  | 16            | mm | -                                       |
|        | r <sub>1s min</sub> | 0.3           | mm | 倒角尺寸                                    |
|        | W                   | 19            | mm | -                                       |
| 接触角    | α                   | 13            |    | -                                       |
| 重量     | m                   | 107           | g  | 质量                                      |
| 基本额定载荷 | C <sub>r</sub>      | 24000         | N  | 基本额定动载荷，径向                              |
|        | C <sub>0r</sub>     | 9100          | N  | 基本额定静载荷，径向<br>轴承座的基本额定载荷                |

### INA GIKPSR12-PS图片

