

FAG 239/600-B-K-MB + AH39/600参数

计算系数	Y_2	5.88		-
基本额定载荷	C_{0r}	8650000	N	基本额定静载荷，径向
计算系数	Y_0	3.86		-
极限转速	n_G	810	r/min	极限转速
参考转速	n_B	435	r/min	参考速度
疲劳极限载荷	C_{ur}	630000	N	疲劳极限载荷，径向
尺寸	d_{1H}	570	mm	-
	D	800	mm	-
	B	150	mm	-
	a	10	mm	-
	b	38	mm	-
	D_1	740.5	mm	-
	$D_{a \max}$	782	mm	-
	d	600	mm	-
	d_{2G}	Tr625x6		-
	$d_{a \min}$	618	mm	-
	d_s	12.5	mm	-
	l	192	mm	-
	n_s	23.5	mm	-
	$r_{a \max}$	4	mm	-
	r_{\min}	5	mm	-
	说明		AH39/600	
重量	m	210000	g	质量
	m_1	55600	g	质量，退卸套
基本额定载荷	C_r	3450000	N	基本额定动载荷，径向
计算系数	e	0.17		-
	Y_1	3.95		-

FAG 239/600-B-K-MB + AH39/600图片



参考资料:<http://www.sozhou.com/p/105f764a.html>