

FAG 32038-X-XL 参数

尺寸	$D_{a \min}$	257	mm	-
	$D_{b \min}$	279	mm	-
	d_1	239	mm	-
	$d_{a \max}$	209	mm	-
	$d_{b \min}$	202	mm	-
	$r_{1, 2 \min}$	3	mm	-
	$r_{3, 4 \min}$	2.5	mm	-
	$r_{a \max}$	3	mm	-
	$r_{b \max}$	2.5	mm	-
重量	m	14600	g	质量
基本额定载荷	C_r	740000	N	基本额定动载荷, 径向
	C_{0r}	1120000	N	基本额定静载荷, 径向
计算系数	e	0.44		-
	Y	1.36		-
	Y_0	0.75		-
疲劳极限载荷	C_{ur}	142000	N	疲劳极限载荷, 径向
极限转速	n_G	2230	r/min	极限转速
参考转速	n_B	1450	r/min	参考速度
说明		T4FD190		根据 DIN ISO 355 的 对应型号
尺寸	d	190	mm	-
	D	290	mm	-
	T	64	mm	-
	a	63.2	mm	-
	B	64	mm	-
	C	48	mm	-
	$C_{a \min}$	10	mm	-
	$C_{b \min}$	16	mm	-

FAG 32038-X-XL图片

