



FAG NJ210-E-TVP2 + HJ210-E参数

尺寸	d	50	mm	-	
	D	90	mm	-	
	B	20	mm	-	
	B <sub>1</sub>	5	mm	-	
	B <sub>2</sub>	9	mm	-	
	D <sub>1</sub>	78.3	mm	-	
	D <sub>a max</sub>	83	mm	-	
	d <sub>1</sub>	64	mm	-	
	d <sub>a max</sub>	58	mm	-	
	d <sub>a min</sub>	57	mm	-	
	d <sub>c min</sub>	67	mm	-	
	E	81.5	mm	-	
	F	59.5	mm	-	
	r <sub>1 min</sub>	1.1	mm	-	
	r <sub>a max</sub>	1	mm	-	
	r <sub>al max</sub>	1	mm	-	
	r <sub>min</sub>	1.1	mm	-	
	s	1.3	mm	距离中心位置的轴向偏移	
	说明		HJ210-E		型号, L 型圈
	重量	m	503	g	质量
m <sub>1</sub>		60	g	质量, L 型圈	
基本额定载荷	C <sub>r</sub>	75000	N	基本额定动载荷, 径向	
	C <sub>0r</sub>	69000	N	基本额定静载荷, 径向	
极限转速	n <sub>G</sub>	9700	r/min	极限转速	
参考转速	n <sub>B</sub>	6700	r/min	参考速度	
疲劳极限载荷	C <sub>ur</sub>	11100	N	疲劳极限载荷, 径向	

FAG NJ210-E-TVP2 + HJ210-E图片



参考资料:<http://www.sozhou.com/p/15a4934d.html>

