

FAG 32219-A参数

尺寸	d	95	mm	-
	D	170	mm	-
	T	45.5	mm	-
	a	39	mm	-
	B	43	mm	-
	C	37	mm	-
	$C_{a \min}$	5	mm	-
	$C_{b \min}$	8.5	mm	-
	$r_{a \max}$	3	mm	-
	$r_{b \max}$	2.5	mm	-
重量	m	4590	g	质量
基本额定载荷	C_r	300000	N	基本额定动载荷，径向
	C_{0r}	415000	N	基本额定静载荷，径向
计算系数	e	0.42		-
	Y	1.43		-
	Y_0	0.79		-
疲劳极限载荷	C_{ur}	48500	N	疲劳极限载荷，径向
极限转速	n_G	4100	r/min	极限转速
参考转速	n_B	2700	r/min	参考速度
说明		T3FC095		根据 DIN ISO 355 的 对应型号
尺寸	$D_{a \max}$	158	mm	-
	$D_{a \min}$	145	mm	-
	$D_{b \min}$	161	mm	-
	d_1	129.6	mm	-
	$d_{a \max}$	108	mm	-
	$d_{b \min}$	107	mm	-
	$r_{1, 2 \min}$	3	mm	-

FAG 32219-A图片

