

### FAG 22215-E1-K参数

尺寸	d	75	mm	-
	D	130	mm	-
	B	31	mm	-
	D <sub>1</sub>	117.7	mm	-
	D <sub>a max</sub>	121	mm	-
	d <sub>2</sub>	89.8	mm	-
	d <sub>a min</sub>	84	mm	-
	d <sub>s</sub>	3.2	mm	-
	n <sub>s</sub>	6.5	mm	-
	r <sub>a max</sub>	1.5	mm	-
	r <sub>min</sub>	1.5	mm	-
	重量	m	1680	g
基本额定载荷	C <sub>r</sub>	216000	N	基本额定动载荷，径向
尺寸	e	0.22		-
计算系数	Y <sub>1</sub>	3.1		-
	Y <sub>2</sub>	4.62		-
基本额定载荷	C <sub>0r</sub>	237000	N	基本额定静载荷，径向
计算系数	Y <sub>0</sub>	3.03		-
极限转速	n <sub>G</sub>	6500	r/min	极限转速
参考转速	n <sub>B</sub>	3900	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	29500	N	疲劳极限载荷，径向

### FAG 22215-E1-K图片



参考资料:<http://www.sozhou.com/p/1710ef16.html>