

FAG 22215-E1-K + AH315G参数

尺寸	$D_{a\ max}$	121	mm	-
	d	75	mm	-
	d_2	89.8	mm	-
	d_{2G}	M80x2		-
	$d_{a\ min}$	84	mm	-
	d_s	3.2	mm	-
	l	45	mm	-
	n_s	6.5	mm	-
	$r_{a\ max}$	1.5	mm	-
	r_{min}	1.5	mm	-
说明		AH315G		型号, 退卸套
重量	m	1680	g	质量
	m_1	290	g	质量, 退卸套
基本额定载荷	C_r	216000	N	基本额定动载荷, 径向
尺寸	e	0.22		-
计算系数	Y_1	3.1		-
	Y_2	4.62		-
基本额定载荷	C_{0r}	237000	N	基本额定静载荷, 径向
计算系数	Y_0	3.03		-
极限转速	n_G	6500	r/min	极限转速
参考转速	n_B	3900	r/min	参考速度
疲劳极限载荷	C_{ur}	29500	N	疲劳极限载荷, 径向
尺寸	d_{1H}	70	mm	-
	D	130	mm	-
	B	31	mm	-
	a	4	mm	-
	b	8	mm	-
	D_1	117.7	mm	-

FAG 22215-E1-K + AH315G图片



参考资料:<http://www.sozhou.com/p/1bd30a3a.html>