

## NSK NU264参数

|        |      |           |       |      |
|--------|------|-----------|-------|------|
| 型号     | 型号   | NU264     |       | -    |
| 外形尺寸   | SD   | 320       | mm    | 内径   |
|        | D    | 580       | mm    | 外径   |
|        | B    | 92        | mm    | 宽度   |
|        | R    | 5.0       | mm    | (最小) |
|        | R1   | 5.0       | mm    | (最小) |
|        | FW   | 390.0     | mm    | -    |
|        | EW   | 0.0       | mm    | -    |
| 基本额定载荷 | CR1  | 1540000   | N     | 动载荷  |
|        | COR1 | 2270000   | N     | 静载荷  |
|        | CR2  | 157000    | kgf   | 动载荷  |
|        | COR2 | 231000    | kgf   | 静载荷  |
| 极限转速   | LG   | 950       | 1/min | 脂润滑  |
|        | LO   | 1200      | 1/min | 油润滑  |
| 安装尺寸   | DA1  | 340.0     | mm    | (最小) |
|        | DBB1 | 340.00000 | mm    | (最小) |
|        | DBB2 | 384       | mm    | (最大) |
|        | DC   | 394       | mm    | (最小) |
|        | DD1  | 420       | mm    | (最小) |
|        | DA2  | 560.0     | mm    | (最大) |
|        | DB1  | 0.0       | mm    | (最小) |
|        | DB2  | 0.0       | mm    | (最小) |
|        | RA   | 4.0       | mm    | (最大) |
|        | RB   | 4.0       | mm    | (最大) |
| 重量     | MASS | 112000    | g     | 重量   |

## NSK NU264图片

参考资料:<http://www.sozhou.com/p/1f917feb.html>

