

FAG 7219-B-JP参数

| | | | | |
|--------|---------------------|--------|-------|------------|
| 尺寸 | B | 32 | mm | - |
| | a | 72 | mm | - |
| | D ₁ | 141.5 | mm | - |
| | D _{a max} | 158 | mm | - |
| | D _{b max} | 163 | mm | - |
| | d ₁ | 125.3 | mm | - |
| | d _{a min} | 107 | mm | - |
| | r _{1 min} | 1.1 | mm | - |
| | r _{a max} | 2.1 | mm | - |
| | r _{a1 max} | 1 | mm | - |
| | r _{min} | 2.1 | mm | - |
| | 重量 | m | 2640 | g |
| 基本额定载荷 | C _r | 123000 | N | 基本额定动载荷，径向 |
| 计算系数 | e | 1.14 | | - |
| | X | 0.35 | | - |
| | Y | 0.57 | | - |
| 尺寸 | d | 95 | mm | - |
| | D | 170 | mm | - |
| 计算系数 | Y ₀ | 0.26 | | - |
| 基本额定载荷 | C _{0r} | 106000 | N | 基本额定静载荷，径向 |
| 极限转速 | n _G | 4700 | r/min | 极限转速 |
| 参考转速 | n _B | 4450 | r/min | 参考速度 |
| 疲劳极限载荷 | C _{ur} | 6200 | N | 疲劳极限载荷，径向 |

FAG 7219-B-JP图片



参考资料: <http://www.sozhou.com/p/243d9b91.html>