

FAG 32020-X参数

计算系数	e	0.46		-	
	Y	1.31		-	
	Y_0	0.72		-	
疲劳极限载荷	C_{ur}	33500	N	疲劳极限载荷，径向	
极限转速	n_G	4500	r/min	极限转速	
参考转速	n_B	2900	r/min	参考速度	
说明		T4CC100		根据 DIN ISO 355 的 对应型号	
尺寸	d	100	mm	-	
	D	150	mm	-	
	T	32	mm	-	
	a	33	mm	-	
	B	32	mm	-	
	C	24	mm	-	
	$C_{a \min}$	6	mm	-	
	$C_{b \min}$	8	mm	-	
	$D_{a \max}$	141	mm	-	
	$D_{a \min}$	134	mm	-	
	$D_{b \min}$	144	mm	-	
	d_1	126.6	mm	-	
	$d_{a \max}$	109	mm	-	
	$d_{b \min}$	109	mm	-	
	$r_{1, 2 \min}$	2	mm	-	
	$r_{3, 4 \min}$	1.5	mm	-	
	$r_{a \max}$	2	mm	-	
	$r_{b \max}$	1.5	mm	-	
	重量	m	1930	g	质量
	基本额定载荷	C_R	173000	N	基本额定动载荷，径向

FAG 32020-X图片

