

NACHI 5312NR参数

| | | | | |
|-----------|----------|---------|-------|------|
| 外形尺寸 | d | 60 | mm | 内径 |
| | D | 130 | mm | 外径 |
| | B | 54 | mm | 宽度 |
| | r | 2.1~4 | mm | 轴向 |
| | r | 2.1~6.5 | mm | 轴向 |
| 止动槽和止动环尺寸 | D1 (max) | 125.22 | mm | (最大) |
| | a (max) | 4.06 | mm | (最大) |
| | b (max) | 3.1 | mm | (最大) |
| | D2 (max) | 139.7 | mm | (最大) |
| | f (max) | 2.82 | mm | (最大) |
| 安装尺寸 | da (min) | 72 | mm | (最小) |
| | Da (max) | 118 | mm | (最大) |
| | ra (max) | 2 | mm | (最大) |
| | Dx (min) | 141.5 | mm | (最小) |
| | Cy (max) | 6.5 | mm | (最大) |
| 重量 | Mass | 3160 | g | 重量 |
| 基本额定载荷 | Cr | 128000 | N | 动载荷 |
| | Cor | 101000 | N | 静载荷 |
| 极限速度 | Grease | 3800 | r/min | 脂润滑 |
| | Oil | 5000 | r/min | 油润滑 |

NACHI 5312NR图片

参考资料:<http://www.sozhou.com/p/2603922d.html>

