

FAG 30330-A参数

尺寸	$r_{3, 4 \text{ min}}$	4	mm	-	
	$r_{a \text{ max}}$	5	mm	-	
	$r_{b \text{ max}}$	4	mm	-	
	d	150	mm	-	
	D	320	mm	-	
	T	72	mm	-	
	a	60	mm	-	
	B	65	mm	-	
	C	55	mm	-	
	$C_{a \text{ min}}$	9	mm	-	
	$C_{b \text{ min}}$	17	mm	-	
	$D_{a \text{ max}}$	302	mm	-	
	$D_{a \text{ min}}$	273	mm	-	
	$D_{b \text{ min}}$	292	mm	-	
	d_1	224	mm	-	
	$d_{a \text{ max}}$	189	mm	-	
	$d_{b \text{ min}}$	168	mm	-	
	$r_{1, 2 \text{ min}}$	5	mm	-	
	重量	m	25100	g	质量
	基本额定载荷	C_r	800000	N	基本额定动载荷，径向
C_{0r}		1030000	N	基本额定静载荷，径向	
计算系数	e	0.35		-	
	Y	1.74		-	
	Y_0	0.96		-	
疲劳极限载荷	C_{ur}	113000	N	疲劳极限载荷，径向	
极限转速	n_G	2270	r/min	极限转速	
参考转速	n_B	1640	r/min	参考速度	

FAG 30330-A图片

