

### FAG NUP2203-E-TVP2参数

|        |               |       |       |             |
|--------|---------------|-------|-------|-------------|
| 尺寸     | s             | 0     | mm    | 距离中心位置的轴向偏移 |
| 重量     | m             | 55    | g     | 质量          |
| 基本额定载荷 | $C_r$         | 28500 | N     | 基本额定动载荷，径向  |
|        | $C_{0r}$      | 21900 | N     | 基本额定静载荷，径向  |
| 极限转速   | $n_G$         | 22900 | r/min | 极限转速        |
| 参考转速   | $n_B$         | 13300 | r/min | 参考速度        |
| 疲劳极限载荷 | $C_{ur}$      | 3500  | N     | 疲劳极限载荷，径向   |
| 尺寸     | d             | 17    | mm    | -           |
|        | D             | 40    | mm    | -           |
|        | B             | 16    | mm    | -           |
|        | $B_3$         | 3     | mm    | -           |
|        | $D_1$         | 32.5  | mm    | -           |
|        | $D_{a\ max}$  | 36    | mm    | -           |
|        | $d_1$         | 24.7  | mm    | -           |
|        | $d_{a\ max}$  | 21.5  | mm    | -           |
|        | $d_{a\ min}$  | 21    | mm    | -           |
|        | $d_{c\ min}$  | 26    | mm    | -           |
|        | F             | 22.1  | mm    | -           |
|        | $r_{1\ min}$  | 0.6   | mm    | -           |
|        | $r_{a\ max}$  | 0.6   | mm    | -           |
|        | $r_{al\ max}$ | 0.6   | mm    | -           |
|        | $r_{min}$     | 0.6   | mm    | -           |

### FAG NUP2203-E-TVP2图片



参考资料:<http://www.sozhou.com/p/2b224868.html>

