


SKF BSD 50100 C参数

主要尺寸	d	50	mm	-
	D	100	mm	-
	H	20	mm	-
基本额定载荷	C	67000	N	动载荷
	C_0	193000	N	静载荷
疲劳载荷极限	P_u	7200	N	-
可达转速	Grease lubrication	5600	r/min	-
	Oil-air lubrication	6700	r/min	-
重量	重量	710	g	-
型号	型号	BSD 50100 C	-	-

SKF BSD 50100 C图片



预载荷等级




	A	B
Preload ¹⁾ [N]	6200	12400
Frictional moment ¹⁾ [Nm] (guideline value)	0,52	0,97
Static axial stiffness ¹⁾ [N/μm] (guideline value)	1550	1970

Max. axial load carrying capacity
(guideline value)
107,4

Reference grease quantity [cm³]
 G_{ref} 6,5

¹⁾ Values apply to unmounted bearing set with two bearings arranged back-to-back or face-to-face

参考资料: <http://www.sozhou.com/p/2c498a5e.html>



预载荷等级

	A	B
Preload¹⁾ [N]	6200	12400
Frictional moment¹⁾ [Nm] (guideline value)	0,52	0,97
Static axial stiffness¹⁾ [N/μm] (guideline value)	1550	1970

Max. axial load carrying capacity
(guideline value)
107,4

Reference grease quantity [cm³]
G_{ref} 6,5

Preload¹⁾ [N]

Frictional moment¹⁾ [Nm]
(guideline value)

Static axial stiffness¹⁾ [N/μm]
(guideline value)

¹⁾ Values apply to unmounted bearing set with two bearings arranged back-to-back or face-to-face