

### FAG NUP2322-E-TVP2参数

尺寸	d	110	mm	-
	D	240	mm	-
	B	80	mm	-
	B <sub>3</sub>	12.5	mm	-
	D <sub>1</sub>	200.9	mm	-
	D <sub>a max</sub>	226	mm	-
	d <sub>1</sub>	155.6	mm	-
	d <sub>a max</sub>	140	mm	-
	d <sub>a min</sub>	124	mm	-
	d <sub>c min</sub>	158	mm	-
	F	143	mm	-
	r <sub>1 min</sub>	3	mm	-
	r <sub>a max</sub>	2.5	mm	-
	r <sub>al max</sub>	2.5	mm	-
	r <sub>min</sub>	3	mm	-
重量	m	17200	g	质量
基本额定载荷	C <sub>r</sub>	750000	N	基本额定动载荷，径向
	C <sub>0r</sub>	800000	N	基本额定静载荷，径向
极限转速	n <sub>G</sub>	3350	r/min	极限转速
参考转速	n <sub>B</sub>	2320	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	135000	N	疲劳极限载荷，径向

### FAG NUP2322-E-TVP2图片



参考资料: <http://www.sozhou.com/p/3235e752.html>

