

### FAG 32926参数

基本额定载荷	$C_{0r}$	370000	N	基本额定静载荷，径向
计算系数	e	0.34		-
	Y	1.77		-
	$Y_0$	0.97		-
疲劳极限载荷	$C_{ur}$	41500	N	疲劳极限载荷，径向
极限转速	$n_G$	3750	r/min	极限转速
参考转速	$n_B$	2220	r/min	参考速度
说明		T2CC130		根据 DIN ISO 355 的 对应型号
尺寸	d	130	mm	-
	D	180	mm	-
	T	32	mm	-
	a	32	mm	-
	B	32	mm	-
	C	25	mm	-
	$C_{a \min}$	6	mm	-
	$C_{b \min}$	7	mm	-
	$D_{a \max}$	171	mm	-
	$D_{a \min}$	167	mm	-
	$D_{b \min}$	173	mm	-
	$d_1$	154.7	mm	-
	$d_{a \max}$	141	mm	-
	$d_{b \min}$	139	mm	-
	$r_{1, 2 \min}$	2	mm	-
	$r_{3, 4 \min}$	1.5	mm	-
	$r_{a \max}$	2	mm	-
	$r_{b \max}$	1.5	mm	-
	重量	m	2400	g

FAG 32926图片

