

FAG 239/530-K-MB + H39/530参数

尺寸	$B_{a \min}$	18	mm	-
	c	68	mm	-
	c_1	89	mm	-
	D_1	656.5	mm	-
	$D_{a \max}$	692	mm	-
	D_m	630	mm	-
	d	530	mm	-
	$d_{a \max}$	576	mm	-
	$d_{b \min}$	546	mm	-
	d_s	12.5	mm	-
	l	216	mm	-
	n_s	23.5	mm	-
	$r_{a \max}$	4	mm	-
	r_{\min}	5	mm	-
说明		H39/530		质量, 紧定套
重量	m	146000	g	质量
	m_1	89000	g	质量, 紧定套
基本额定载荷	C_r	2850000	N	基本额定动载荷, 径向
计算系数	e	0.18		-
	Y_1	3.85		-
	Y_2	5.73		-
基本额定载荷	C_{0r}	6800000	N	基本额定静载荷, 径向
计算系数	Y_0	3.76		-
极限转速	n_G	930	r/min	极限转速
参考转速	n_B	510	r/min	参考速度
疲劳极限载荷	C_{ur}	385000	N	疲劳极限载荷, 径向
尺寸	d_{1H}	500	mm	-

D	710	mm	-
B	136	mm	-

FAG 239/530-K-MB + H39/530图片

