

FAG 30322-A参数

尺寸	d	110	mm	-	
	D	240	mm	-	
	T	54.5	mm	-	
	a	45	mm	-	
	B	50	mm	-	
	C	42	mm	-	
	$C_{a \min}$	8	mm	-	
	$C_{b \min}$	12.5	mm	-	
	$D_{a \max}$	226	mm	-	
	$D_{a \min}$	206	mm	-	
	$D_{b \min}$	220	mm	-	
	d_1	169.2	mm	-	
	$d_{a \max}$	141	mm	-	
	$d_{b \min}$	124	mm	-	
	$r_{1, 2 \min}$	4	mm	-	
	$r_{a \max}$	4	mm	-	
	$r_{b \max}$	3	mm	-	
	重量	m	11000	g	质量
	基本额定载荷	C_r	480000	N	基本额定动载荷, 径向
C_{0r}		590000	N	基本额定静载荷, 径向	
计算系数	e	0.35		-	
	Y	1.74		-	
	Y_0	0.96		-	
疲劳极限载荷	C_{ur}	71000	N	疲劳极限载荷, 径向	
极限转速	n_G	3050	r/min	极限转速	
参考转速	n_B	2410	r/min	参考速度	
说明		T2GB110		根据 DIN ISO 355 的 对应型号	

FAG 30322-A图片

