

## FAG 32004-X参数

疲劳极限载荷	$C_{ur}$	3000	N	疲劳极限载荷，径向	
极限转速	$n_G$	18100	r/min	极限转速	
参考转速	$n_B$	10900	r/min	参考速度	
说明		T3CC020		根据 DIN ISO 355 的 对应型号	
尺寸	d	20	mm	-	
	D	42	mm	-	
	T	15	mm	-	
	a	10	mm	-	
	B	15	mm	-	
	C	12	mm	-	
	$C_{a \min}$	3	mm	-	
	$C_{b \min}$	3	mm	-	
	$D_{a \max}$	37	mm	-	
	$D_{a \min}$	36	mm	-	
	$D_{b \min}$	39	mm	-	
	$d_1$	33	mm	-	
	$d_{a \max}$	25	mm	-	
	$d_{b \min}$	25	mm	-	
	$r_{1, 2 \min}$	0.6	mm	-	
	$r_{3, 4 \min}$	0.6	mm	-	
	$r_{a \max}$	0.6	mm	-	
	$r_{b \max}$	0.6	mm	-	
	重量	m	108	g	质量
	基本额定载荷	$C_r$	24000	N	基本额定动载荷，径向
$C_{0r}$		28500	N	基本额定静载荷，径向	
计算系数	e	0.37		-	
	Y	1.6		-	

FAG 32004-X图片

