

INA GIKSL18-PS参数

| | | | | |
|--------|---------------------|---------------|----|---|
| 尺寸 | d | 18 | mm | 轴承座孔径公差：H7 (算术平均值) 公差： +0,018 / 0 |
| | d _{2 max} | 47 | mm | - |
| | l ₄ | 94.5 | mm | - |
| 说明 | | 0.005 - 0.045 | mm | 径向内部游隙 |
| 尺寸 | B | 23 | mm | 公差：0 / -0,12 |
| | C ₁ | 16.5 | mm | - |
| | D | 35 | mm | - |
| | d ₁ | 21.8 | mm | - |
| | d ₃ | M18x1.5 | | - |
| | d ₄ | 25 | mm | - |
| | d ₅ | 31 | mm | - |
| | d _K | 31.7 | mm | - |
| | h ₁ | 71 | mm | - |
| | l _{3 min} | 27 | mm | - |
| | l ₅ | 10 | mm | - |
| | l _{7 min} | 23 | mm | - |
| | r _{1s min} | 0.3 | mm | 倒角尺寸 |
| | W | 27 | mm | - |
| 接触角 | α | 15 | | - |
| 重量 | m | 295 | g | 质量 |
| 基本额定载荷 | C _r | 47500 | N | 基本额定动载荷，径向 |
| | C _{0r} | 23000 | N | 基本额定静载荷，径向 轴承座的基本额定载荷 |

INA GIKSL18-PS图片

