

NTN KRT26XLL/3AS参数

| 型号 | ORDER | KRT26XLL/3AS | | 型号 |
|--------|-------|--------------|-------|-----|
| 尺寸 | D | 26 | mm | - |
| | D1 | 10 | mm | - |
| | C | 12 | mm | - |
| | F | 12 | mm | - |
| | B | 13.0 | mm | - |
| | B1 | 36 | mm | - |
| | B2 | 23.0 | mm | - |
| | G | M10x1.25 | | 螺栓 |
| | G1 | 12 | mm | - |
| | C1 | 0.6 | mm | - |
| | E | 17 | mm | - |
| 基本额定载荷 | CR | 5300 | N | 动载荷 |
| | COR | 6650 | N | 静载荷 |
| | CRF | 540 | kgf | 动载荷 |
| | CORF | 680 | kgf | 静载荷 |
| | CR2 | 6100 | N | 动载荷 |
| | COR2 | 6100 | N | 静载荷 |
| | CRF2 | 620 | kgf | 动载荷 |
| | CORF2 | 620 | kgf | 静载荷 |
| 极限转速 | LSG | 12000 | r/min | 脂润滑 |
| | LSO | 16000 | r/min | 油润滑 |
| 重量 | MASS | 59 | g | 重量 |

NTN KRT26XLL/3AS图片

参考资料:<http://www.sozhou.com/p/39ce72aa.html>

