

NACHI 6926N参数

| | | | | |
|-----------|----------|-------|-------|------|
| 外形尺寸 | d | 130 | mm | 内径 |
| | D | 180 | mm | 外径 |
| | B | 24 | mm | 宽度 |
| | r | 1.5~3 | mm | 轴向 |
| | r | 1.5~5 | mm | 轴向 |
| | r1 | 0.5~ | mm | 径向 |
| | r1 | 0.5~ | mm | 径向 |
| 止动槽和止动环尺寸 | D1 | 176.8 | mm | (最大) |
| | a | 3.7 | mm | (最大) |
| | b | 1.9 | mm | (最小) |
| | D2 | 186.5 | mm | (最大) |
| | f | 1.7 | mm | (最大) |
| 安装尺寸 | da (min) | 137 | mm | (最小) |
| | Da (max) | 173 | mm | (最大) |
| | Dx (min) | 188 | mm | (最小) |
| | ra (max) | 1.5 | mm | (最大) |
| | Cy (max) | 5.1 | mm | (最大) |
| 基本额定载荷 | Cr | 65000 | N | 动载荷 |
| | Cor | 67000 | N | 静载荷 |
| 极限速度 | Grease | 3500 | r/min | 脂润滑 |
| | Oil | 4200 | r/min | 油润滑 |

NACHI 6926N图片

参考资料:<http://www.sozhou.com/p/3d436a7f.html>

