

**FAG B71916-E-2RSD-T-P4S参数**

|        |               |       |       |            |
|--------|---------------|-------|-------|------------|
| 尺寸     | $r_{a\ max}$  | 0.6   | mm    | -          |
|        | $r_{al\ max}$ | 0.6   | mm    | -          |
|        | $r_{min}$     | 1     | mm    | -          |
| 重量     | m             | 390   | g     | 质量         |
| 基本额定载荷 | $C_r$         | 33500 | N     | 基本额定动载荷，径向 |
|        | $C_{0r}$      | 24000 | N     | 基本额定静载荷，径向 |
| 极限转速   | $n_{G\ Fett}$ | 11000 | r/min | 脂润滑时的极限转速  |
| 疲劳极限载荷 | $C_{ur}$      | 2470  | N     | 疲劳极限载荷，径向  |
| 尺寸     | d             | 80    | mm    | -          |
|        | D             | 110   | mm    | -          |
|        | B             | 16    | mm    | -          |
|        | a             | 30    | mm    | -          |
|        | $D_a\ H12$    | 104   | mm    | -          |
|        | $d_a\ h12$    | 86    | mm    | -          |
|        | $r_{l\ min}$  | 1     | mm    | -          |

**FAG B71916-E-2RSD-T-P4S图片**



