

FAG 22217-E1-K + AHX317参数

尺寸	a	4	mm	-
	b	9	mm	-
	D ₁	135.4	mm	-
	D _{a max}	139	mm	-
	d	85	mm	-
	d ₂	99.7	mm	-
	d _{2G}	M95x2		-
	d _{a min}	96	mm	-
	d _s	3.2	mm	-
	l	52	mm	-
	n _s	6.5	mm	-
	r _{a max}	2	mm	-
	r _{min}	2	mm	-
	说明		AHX317	
重量	m	2590	g	质量
	m ₁	440	g	质量, 退卸套
基本额定载荷	C _r	305000	N	基本额定动载荷, 径向
尺寸	e	0.22		-
计算系数	Y ₁	3.04		-
	Y ₂	4.53		-
基本额定载荷	C _{0r}	325000	N	基本额定静载荷, 径向
计算系数	Y ₀	2.97		-
极限转速	n _G	5700	r/min	极限转速
参考转速	n _B	3550	r/min	参考速度
疲劳极限载荷	C _{ur}	38000	N	疲劳极限载荷, 径向
尺寸	d _{1H}	80	mm	-
	D	150	mm	-
	B	36	mm	-

FAG 22217-E1-K + AHX317图片



参考资料:<http://www.sozhou.com/p/4984f778.html>