

FAG 230/560-B-K-MB + AH30/560A参数

疲劳极限载荷	$C_{ur}$	740000	N	疲劳极限载荷，径向	
尺寸	$d_{1H}$	530	mm	-	
	D	820	mm	-	
	B	195	mm	-	
	a	12	mm	-	
	b	45	mm	-	
	$D_1$	741.5	mm	-	
	$D_{a\ max}$	797	mm	-	
	d	560	mm	-	
	$d_{2G}$	Tr590x6		-	
	$d_{a\ min}$	583	mm	-	
	$d_s$	12.5	mm	-	
	l	240	mm	-	
	$n_s$	23.5	mm	-	
	$r_{a\ max}$	5	mm	-	
	$r_{min}$	6	mm	-	
	说明		AH30/560A		型号，退卸套
	重量	m	339000	g	质量
$m_1$		68400	g	质量，退卸套	
基本额定载荷	$C_r$	5100000	N	基本额定动载荷，径向	
计算系数	e	0.23		-	
	$Y_1$	2.95		-	
	$Y_2$	4.4		-	
基本额定载荷	$C_{0r}$	11000000	N	基本额定静载荷，径向	
计算系数	$Y_0$	2.89		-	
极限转速	$n_G$	770	r/min	极限转速	
参考转速	$n_B$	450	r/min	参考速度	

FAG 230/560-B-K-MB + AH30/560A图片



参考资料:<http://www.sozhou.com/p/4a4ba131.html>