

FAG 32016-X-XL 参数

尺寸	d	80	mm	-	
	D	125	mm	-	
	T	29	mm	-	
	a	27.2	mm	-	
	B	29	mm	-	
	C	22	mm	-	
	$C_{a \min}$	6	mm	-	
	$C_{b \min}$	7	mm	-	
	$D_{a \max}$	117	mm	-	
	$D_{a \min}$	112	mm	-	
	$D_{b \min}$	120	mm	-	
	d_1	104.2	mm	-	
	$d_{a \max}$	89	mm	-	
	$d_{b \min}$	87	mm	-	
	$r_{1, 2 \min}$	1.5	mm	-	
	$r_{3, 4 \min}$	1.5	mm	-	
	$r_{a \max}$	1.5	mm	-	
	$r_{b \max}$	1.5	mm	-	
	重量	m	1290	g	质量
	基本额定载荷	C_r	162000	N	基本额定动载荷, 径向
C_{0r}		212000	N	基本额定静载荷, 径向	
计算系数	e	0.42		-	
	Y	1.42		-	
	Y_0	0.78		-	
疲劳极限载荷	C_{ur}	32500	N	疲劳极限载荷, 径向	
极限转速	n_G	5500	r/min	极限转速	
参考转速	n_B	3450	r/min	参考速度	

FAG 32016-X-XL图片

