

FAG 23252-B-K-MB + AH2352G参数

尺寸	$d_{1H}$	240	mm	-
	D	480	mm	-
	B	174	mm	-
	a	8	mm	-
	b	30	mm	-
	$D_1$	405.4	mm	-
	$D_{a\ max}$	460	mm	-
	d	260	mm	-
	$d_{2G}$	Tr280x4		-
	$d_{a\ min}$	280	mm	-
	$d_s$	12.5	mm	-
	l	205	mm	-
	$n_s$	23.5	mm	-
	$r_{a\ max}$	4	mm	-
	$r_{min}$	5	mm	-
说明		AH2352G		型号, 退卸套
重量	m	138000	g	质量
	$m_1$	18700	g	质量, 退卸套
基本额定载荷	$C_r$	2900000	N	基本额定动载荷, 径向
计算系数	e	0.37		-
疲劳极限载荷	$C_{ur}$	270000	N	疲劳极限载荷, 径向
计算系数	$Y_1$	1.8		-
	$Y_2$	2.69		-
基本额定载荷	$C_{0r}$	4900000	N	基本额定静载荷, 径向
计算系数	$Y_0$	1.76		-
极限转速	$n_G$	1330	r/min	极限转速
参考转速	$n_B$	670	r/min	参考速度

FAG 23252-B-K-MB + AH2352G图片



参考资料:<http://www.sozhou.com/p/4b4027fa.html>