

FAG NJ2217-E-TVP2参数

尺寸	D_1	131.5	mm	-	
	$D_{a\ max}$	139	mm	-	
	d_1	107.5	mm	-	
	$d_{a\ max}$	99	mm	-	
	$d_{a\ min}$	96	mm	-	
	$d_{c\ min}$	110	mm	-	
	F	100.5	mm	-	
	$r_{1\ min}$	2	mm	-	
	$r_{a\ max}$	2	mm	-	
	$r_{al\ max}$	2	mm	-	
	r_{min}	2	mm	-	
		s	1.3	mm	距离中心位置的轴向偏移
	重量	m	2550	g	质量
基本额定载荷	C_r	255000	N	基本额定动载荷，径向	
	C_{0r}	275000	N	基本额定静载荷，径向	
极限转速	n_G	5600	r/min	极限转速	
参考转速	n_B	3350	r/min	参考速度	
疲劳极限载荷	C_{ur}	48500	N	疲劳极限载荷，径向	
尺寸	d	85	mm	-	
	D	150	mm	-	
	B	36	mm	-	
	B_1	8	mm	-	
	B_2	13	mm	-	

FAG NJ2217-E-TVP2图片





参考资料:<http://www.sozhou.com/p/56079f4a.html>