

FAG 320/32-X参数

参考转速	n_B	7500	r/min	参考速度	
说明		T4CC032		根据 DIN ISO 355 的 对应型号	
尺寸	d	32	mm	-	
	D	58	mm	-	
	T	17	mm	-	
	a	14	mm	-	
	B	17	mm	-	
	C	13	mm	-	
	$C_a \text{ min}$	3	mm	-	
	$C_b \text{ min}$	4	mm	-	
	$D_a \text{ max}$	52	mm	-	
	$D_a \text{ min}$	50	mm	-	
	$D_b \text{ min}$	55	mm	-	
	d_1	46.5	mm	-	
	$d_a \text{ max}$	38	mm	-	
	$d_b \text{ min}$	38	mm	-	
	$r_{1, 2} \text{ min}$	1	mm	-	
	$r_{3, 4} \text{ min}$	1	mm	-	
	$r_a \text{ max}$	1	mm	-	
	$r_b \text{ max}$	1	mm	-	
	重量	m	197	g	质量
	基本额定载荷	C_r	39000	N	基本额定动载荷, 径向
C_{0r}		48500	N	基本额定静载荷, 径向	
计算系数	e	0.45		-	
	Y	1.32		-	
	Y_0	0.73		-	
疲劳极限载荷	C_{ur}	5600	N	疲劳极限载荷, 径向	

FAG 320/32-X图片

