

### INA GIKSL10-PS参数

尺寸	d	10	mm	轴承座孔径公差：H7 (算术平均值) 公差： +0,015 / 0
	d <sub>2 max</sub>	29	mm	-
	l <sub>4</sub>	57.5	mm	-
说明		0.005 - 0.040	mm	径向内部游隙
尺寸	B	14	mm	公差：0 / -0,12
	C <sub>1</sub>	10.5	mm	-
	D	22	mm	-
	d <sub>1</sub>	12.9	mm	-
	d <sub>3</sub>	M10		-
	d <sub>4</sub>	15	mm	-
	d <sub>5</sub>	19	mm	-
	d <sub>K</sub>	19	mm	-
	h <sub>1</sub>	43	mm	-
	l <sub>3 min</sub>	15	mm	-
	l <sub>5</sub>	6.5	mm	-
	l <sub>7 min</sub>	14	mm	-
	r <sub>1s min</sub>	0.3	mm	倒角尺寸
	W	17	mm	-
接触角	α	13		-
重量	m	72	g	质量
基本额定载荷	C <sub>r</sub>	18000	N	基本额定动载荷，径向
	C <sub>0r</sub>	8000	N	基本额定静载荷，径向 轴承座的基本额定载荷

### INA GIKSL10-PS图片

