

FAG 230/710-B-K-MB + AH30/710A参数

极限转速	n_G	590	r/min	极限转速	
参考转速	n_B	330	r/min	参考速度	
疲劳极限载荷	C_{ur}	1140000	N	疲劳极限载荷, 径向	
尺寸	d_{1H}	670	mm	-	
	D	1030	mm	-	
	B	236	mm	-	
	a	16	mm	-	
	b	50	mm	-	
	D_1	938.8	mm	-	
	$D_{a\ max}$	1002	mm	-	
	d	710	mm	-	
	d_{2G}	Tr750x7		-	
	$d_{a\ min}$	738	mm	-	
	d_s	12.5	mm	-	
	l	286	mm	-	
	n_s	23.5	mm	-	
	$r_{a\ max}$	6	mm	-	
	r_{min}	7.5	mm	-	
	说明		AH30/710A		型号, 退卸套
	重量	m	650000	g	质量
m_1		135000	g	质量, 退卸套	
基本额定载荷	C_r	7650000	N	基本额定动载荷, 径向	
计算系数	e	0.22		-	
	Y_1	3.07		-	
	Y_2	4.57		-	
基本额定载荷	C_{0r}	17000000	N	基本额定静载荷, 径向	
计算系数	Y_0	3		-	

FAG 230/710-B-K-MB + AH30/710A图片



参考资料:<http://www.sozhou.com/p/6027d1a0.html>