

### INA GIKSR30-PS参数

|        |                      |               |    |   |
|--------|----------------------|---------------|----|---|
| 尺寸     | $C_1$                | 25            | mm | -                                       |
|        | D                    | 55            | mm | -                                       |
|        | $d_1$                | 34.8          | mm | -                                       |
|        | $d_3$                | M30x2         |    | -                                       |
|        | $d_4$                | 40            | mm | -                                       |
|        | $d_5$                | 50            | mm | -                                       |
|        | $d_K$                | 50.8          | mm | -                                       |
|        | $h_1$                | 110           | mm | -                                       |
|        | $l_{3 \text{ min}}$  | 45            | mm | -                                       |
|        | $l_5$                | 15            | mm | -                                       |
|        | $l_{7 \text{ min}}$  | 35            | mm | -                                       |
|        | $r_{1s \text{ min}}$ | 0.3           | mm | 倒角尺寸                                    |
|        | W                    | 41            | mm | -                                       |
| 接触角    | $\alpha$             | 15            |    | -                                       |
| 重量     | m                    | 1150          | g  | 质量                                      |
| 基本额定载荷 | $C_r$                | 114000        | N  | 基本额定动载荷，径向                              |
|        | $C_{0r}$             | 47500         | N  | 基本额定静载荷，径向<br>轴承座的基本额定载荷                |
| 尺寸     | d                    | 30            | mm | 轴承座孔径公差：H7<br>(算术平均值) 公差：<br>+0,021 / 0 |
|        | $d_{2 \text{ max}}$  | 71            | mm | -                                       |
|        | $l_4$                | 145.5         | mm | -                                       |
| 说明     |                      | 0.010 - 0.055 | mm | 径向内部游隙                                  |
| 尺寸     | B                    | 37            | mm | 公差：0 / -0,12                            |

### INA GIKSR30-PS图片

