

NSK NJ228参数

| | | | | | |
|--------|------|-----------|-------|------|----|
| 外形尺寸 | R1 | 3.0 | mm | (最小) | |
| | FW | 169.0 | mm | - | |
| | EW | 0.0 | mm | - | |
| 基本额定载荷 | CR1 | 297000 | N | 动载荷 | |
| | COR1 | 375000 | N | 静载荷 | |
| | CR2 | 30500 | kgf | 动载荷 | |
| | COR2 | 38000 | kgf | 静载荷 | |
| 极限转速 | LG | 2400 | 1/min | 脂润滑 | |
| | LO | 3000 | 1/min | 油润滑 | |
| 安装尺寸 | DA1 | 153.0 | mm | (最小) | |
| | DBB1 | 153.00000 | mm | (最小) | |
| | DBB2 | 165 | mm | (最大) | |
| | DC | 171 | mm | (最小) | |
| | DD1 | 182 | mm | (最小) | |
| | DA2 | 237.0 | mm | (最大) | |
| | DB1 | 0.0 | mm | (最小) | |
| | DB2 | 0.0 | mm | (最小) | |
| | RA | 2.5 | mm | (最大) | |
| | RB | 2.5 | mm | (最大) | |
| | 重量 | MASS | 8190 | g | 重量 |
| | 型号 | 型号 | NJ228 | | - |
| | 外形尺寸 | SD | 140 | mm | 内径 |
| D | | 250 | mm | 外径 | |
| B | | 42 | mm | 宽度 | |
| R | | 3.0 | mm | (最小) | |

NSK NJ228图片

参考资料:<http://www.sozhou.com/p/62c2fbd2.html>

