

FAG 22309-E1-K + AH2309参数

尺寸	d_{1H}	40	mm	-	
	D	100	mm	-	
	B	36	mm	-	
	a	3	mm	-	
	b	7	mm	-	
	D_1	84.7	mm	-	
	$D_{a \max}$	91	mm	-	
	d	45	mm	-	
	d_2	58.9	mm	-	
	d_{2G}	M50x1.5		-	
	$d_{a \min}$	54	mm	-	
	d_s	3.2	mm	-	
	l	44	mm	-	
	n_s	6.5	mm	-	
	$r_{a \max}$	1.5	mm	-	
	r_{\min}	1.5	mm	-	
	说明		AH2309		型号, 退卸套
	重量	m	1360	g	质量
		m_1	170	g	质量, 退卸套
	基本额定载荷	C_r	187000	N	基本额定动载荷, 径向
计算系数	e	0.36		-	
	Y_0	1.86		-	
极限转速	n_G	6800	r/min	极限转速	
参考转速	n_B	5300	r/min	参考速度	
计算系数	Y_1	1.9		-	
	Y_2	2.83		-	
基本额定载荷	C_{0r}	183000	N	基本额定静载荷, 径向	
疲劳极限载荷	C_{ur}	16100	N	疲劳极限载荷, 径向	

FAG 22309-E1-K + AH2309图片



参考资料:<http://www.sozhou.com/p/636fd6d0.html>