



FAG NJ2236-E-M1 + HJ2236-E参数

尺寸	d	180	mm	-	
	D	320	mm	-	
	B	86	mm	-	
	B <sub>1</sub>	12	mm	-	
	B <sub>2</sub>	24	mm	-	
	D <sub>1</sub>	280	mm	-	
	D <sub>a max</sub>	303	mm	-	
	d <sub>1</sub>	229	mm	-	
	d <sub>a max</sub>	214	mm	-	
	d <sub>a min</sub>	197	mm	-	
	d <sub>c min</sub>	233	mm	-	
	E	291	mm	-	
	F	215	mm	-	
	r <sub>1 min</sub>	4	mm	-	
	r <sub>a max</sub>	3	mm	-	
	r <sub>al max</sub>	3	mm	-	
	r <sub>min</sub>	4	mm	-	
	s	7.2	mm	距离中心位置的轴向偏移	
	说明		HJ2236-E		型号, L 型圈
	重量	m	31100	g	质量
m <sub>1</sub>		1870	g	质量, L 型圈	
基本额定载荷	C <sub>r</sub>	1180000	N	基本额定动载荷, 径向	
	C <sub>0r</sub>	1490000	N	基本额定静载荷, 径向	
极限转速	n <sub>G</sub>	3200	r/min	极限转速	
参考转速	n <sub>B</sub>	1400	r/min	参考速度	
疲劳极限载荷	C <sub>ur</sub>	225000	N	疲劳极限载荷, 径向	

FAG NJ2236-E-M1 + HJ2236-E图片



参考资料:<http://www.sozhou.com/p/65ac8b42.html>

