

NSK NU1084参数

| | | | | | |
|--------|------|-----------|--------|------|----|
| 外形尺寸 | FW | 470.0 | mm | - | |
| | EW | 570.0 | mm | - | |
| 基本额定载荷 | CR1 | 1390000 | N | 动载荷 | |
| | COR1 | 2380000 | N | 静载荷 | |
| | CR2 | 142000 | kgf | 动载荷 | |
| | COR2 | 243000 | kgf | 静载荷 | |
| 极限转速 | LG | 850 | 1/min | 脂润滑 | |
| | LO | 1100 | 1/min | 油润滑 | |
| 安装尺寸 | DA1 | 440.0 | mm | (最小) | |
| | DBB1 | 440.00000 | mm | (最小) | |
| | DBB2 | 465 | mm | (最大) | |
| | DC | 475 | mm | (最小) | |
| | DD1 | | mm | (最小) | |
| | DA2 | 600.0 | mm | (最大) | |
| | DB1 | 600.0 | mm | (最小) | |
| | DB2 | 574.5 | mm | (最小) | |
| | RA | 4.0 | mm | (最大) | |
| | RB | 4.0 | mm | (最大) | |
| | 重量 | MASS | 91700 | g | 重量 |
| | 型号 | 型号 | NU1084 | | - |
| | 外形尺寸 | SD | 420 | mm | 内径 |
| D | | 620 | mm | 外径 | |
| B | | 90 | mm | 宽度 | |
| R | | 5.0 | mm | (最小) | |
| R1 | | 5.0 | mm | (最小) | |

NSK NU1084图片

参考资料:<http://www.sozhou.com/p/65fa68cf.html>

