

FAG 32316-A参数

说明		T2GD080		根据 DIN ISO 355 的 对应型号
尺寸	d	80	mm	-
	D	170	mm	-
	T	61.5	mm	-
	a	42	mm	-
	B	58	mm	-
	C	48	mm	-
	$C_a \text{ min}$	7	mm	-
	$C_b \text{ min}$	13.5	mm	-
	$D_a \text{ max}$	158	mm	-
	$D_a \text{ min}$	142	mm	-
	$D_b \text{ min}$	159	mm	-
	d_1	122	mm	-
	$d_a \text{ max}$	98	mm	-
	$d_b \text{ min}$	92	mm	-
	$r_{1, 2} \text{ min}$	3	mm	-
	$r_{3, 4} \text{ min}$	2.5	mm	-
	$r_a \text{ max}$	3	mm	-
	$r_b \text{ max}$	2.5	mm	-
重量	m	6570	g	质量
基本额定载荷	C_r	400000	N	基本额定动载荷, 径向
参考转速	n_B	3200	r/min	参考速度
基本额定静载荷	C_{0r}	530000	N	基本额定静载荷, 径向
计算系数	e	0.35		-
	Y	1.74		-
	Y_0	0.96		-
疲劳极限载荷	C_{ur}	63000	N	疲劳极限载荷, 径向

FAG 32316-A图片

