

FAG 31322-X参数

疲劳极限载荷	C_{ur}	71000	N	疲劳极限载荷，径向	
极限转速	n_G	2850	r/min	极限转速	
参考转速	n_B	2240	r/min	参考速度	
说明		T7GB110		根据 DIN ISO 355 的 对应型号	
尺寸	d	110	mm	-	
	D	240	mm	-	
	T	63	mm	-	
	a	75	mm	-	
	B	57	mm	-	
	C	38	mm	-	
	$C_{a \min}$	7	mm	-	
	$C_{b \min}$	25	mm	-	
	$D_{a \max}$	226	mm	-	
	$D_{a \min}$	188	mm	-	
	$D_{b \min}$	224	mm	-	
	d_1	178	mm	-	
	$d_{a \max}$	135	mm	-	
	$d_{b \min}$	124	mm	-	
	$r_{1, 2 \min}$	4	mm	-	
	$r_{3, 4 \min}$	3	mm	-	
	$r_{a \max}$	4	mm	-	
	$r_{b \max}$	3	mm	-	
	重量	m	12300	g	质量
	基本额定载荷	C_r	465000	N	基本额定动载荷，径向
C_{0r}		590000	N	基本额定静载荷，径向	
计算系数	e	0.83		-	
	Y	0.73		-	

FAG 31322-X图片

