

FAG 32214-A参数

尺寸	d	70	mm	-	
	D	125	mm	-	
	T	33.25	mm	-	
	a	28	mm	-	
	B	31	mm	-	
	C	27	mm	-	
	$C_{a \text{ min}}$	4	mm	-	
	$C_{b \text{ min}}$	6	mm	-	
	$D_{a \text{ max}}$	116	mm	-	
	$D_{a \text{ min}}$	108	mm	-	
	$D_{b \text{ min}}$	119	mm	-	
	d_1	96	mm	-	
	$d_{a \text{ max}}$	80	mm	-	
	$d_{b \text{ min}}$	79	mm	-	
	$r_{1, 2 \text{ min}}$	2	mm	-	
	$r_{3, 4 \text{ min}}$	1.5	mm	-	
	$r_{a \text{ max}}$	2	mm	-	
	$r_{b \text{ max}}$	1.5	mm	-	
	重量	m	1660	g	质量
	基本额定载荷	C_r	163000	N	基本额定动载荷, 径向
C_{0r}		214000	N	基本额定静载荷, 径向	
计算系数	e	0.42		-	
	Y	1.43		-	
	Y_0	0.79		-	
疲劳极限载荷	C_{ur}	26500	N	疲劳极限载荷, 径向	
极限转速	n_G	5700	r/min	极限转速	
参考转速	n_B	3400	r/min	参考速度	

FAG 32214-A图片

