

FAG 32313-A参数

计算系数	Y	1.74		-
	Y_0	0.96		-
疲劳极限载荷	C_{ur}	43500	N	疲劳极限载荷，径向
极限转速	n_G	5100	r/min	极限转速
尺寸	C	39	mm	-
	$C_{a \text{ min}}$	6	mm	-
	$C_{b \text{ min}}$	12	mm	-
	$D_{a \text{ max}}$	128	mm	-
	$D_{a \text{ min}}$	117	mm	-
	$D_{b \text{ min}}$	130	mm	-
	d_1	99.6	mm	-
	$d_{a \text{ max}}$	80	mm	-
	$d_{b \text{ min}}$	77	mm	-
	$r_{1, 2 \text{ min}}$	3	mm	-
	$r_{3, 4 \text{ min}}$	2.5	mm	-
	$r_{a \text{ max}}$	3	mm	-
	$r_{b \text{ max}}$	2.5	mm	-
重量	m	3630	g	质量
基本额定载荷	C_r	270000	N	基本额定动载荷，径向
	C_{0r}	345000	N	基本额定静载荷，径向
计算系数	e	0.35		-
尺寸	d	65	mm	-
	D	140	mm	-
	T	51	mm	-
	a	35	mm	-
	B	48	mm	-
参考转速	n_B	3800	r/min	参考速度

FAG 32313-A图片

