

## FAG 32930参数

尺寸	d	150	mm	-
	D	210	mm	-
	T	38	mm	-
	a	36	mm	-
	B	38	mm	-
	C	30	mm	-
	C <sub>a min</sub>	7	mm	-
	C <sub>b min</sub>	8	mm	-
	D <sub>a max</sub>	201	mm	-
	D <sub>a min</sub>	194	mm	-
	D <sub>b min</sub>	202	mm	-
	基本额定载荷	C <sub>r</sub>	285000	N
C <sub>0r</sub>		495000	N	基本额定静载荷，径向
计算系数	e	0.33		-
	Y	1.83		-
	Y <sub>0</sub>	1.01		-
疲劳极限载荷	C <sub>ur</sub>	62000	N	疲劳极限载荷，径向
极限转速	n <sub>G</sub>	3200	r/min	极限转速
参考转速	n <sub>B</sub>	2020	r/min	参考速度
说明		T2DC150		根据 DIN ISO 355 的 对应型号
尺寸	r <sub>a max</sub>	2.5	mm	-
	r <sub>b max</sub>	2	mm	-
重量	m	3900	g	质量
尺寸	d <sub>1</sub>	177.8	mm	-
	d <sub>a max</sub>	162	mm	-
	d <sub>b min</sub>	160	mm	-
	r <sub>1, 2 min</sub>	2.5	mm	-

FAG 32930图片

