

### INA GIKSL25-PS参数

尺寸	d	25	mm	轴承座孔径公差：H7 (算术平均值) 公差： +0,021 / 0
	d <sub>2 max</sub>	61	mm	-
	l <sub>4</sub>	124.5	mm	-
说明		0.010 - 0.055	mm	径向内部游隙
尺寸	B	31	mm	公差：0 / -0,12
	C <sub>1</sub>	22	mm	-
	D	47	mm	-
	d <sub>1</sub>	29.5	mm	-
	d <sub>3</sub>	M24x2		-
	d <sub>4</sub>	33.5	mm	-
	d <sub>5</sub>	42	mm	-
	d <sub>K</sub>	42.8	mm	-
	h <sub>1</sub>	94	mm	-
	l <sub>3 min</sub>	36	mm	-
	l <sub>5</sub>	12	mm	-
	l <sub>7 min</sub>	30	mm	-
	r <sub>1s min</sub>	0.3	mm	倒角尺寸
	W	36	mm	-
接触角	α	15		-
重量	m	650	g	质量
基本额定载荷	C <sub>r</sub>	85000	N	基本额定动载荷，径向
	C <sub>0r</sub>	36200	N	基本额定静载荷，径向 轴承座的基本额定载荷

### INA GIKSL25-PS图片

