


### FAG NJ409-M1 参数

尺寸	d	45	mm	-
	D	120	mm	-
	B	29	mm	-
	B <sub>1</sub>	8	mm	-
	B <sub>2</sub>	13.5	mm	-
	D <sub>1</sub>	94.6	mm	-
	D <sub>a max</sub>	107	mm	-
	d <sub>1</sub>	71.6	mm	-
	d <sub>a max</sub>	63	mm	-
	d <sub>a min</sub>	58	mm	-
	d <sub>c min</sub>	74	mm	-
	F	64.5	mm	-
	r <sub>1 min</sub>	2	mm	-
	r <sub>a max</sub>	2	mm	-
	r <sub>a1 max</sub>	2	mm	-
	r <sub>min</sub>	2	mm	-
	s	2.9	mm	距离中心位置的轴向偏移
重量	m	1900	g	质量
基本额定载荷	C <sub>r</sub>	143000	N	基本额定动载荷，径向
	C <sub>0r</sub>	119000	N	基本额定静载荷，径向
极限转速	n <sub>G</sub>	9600	r/min	极限转速
参考转速	n <sub>B</sub>	5900	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	21400	N	疲劳极限载荷，径向

### FAG NJ409-M1 图片





参考资料:<http://www.sozhou.com/p/99778ea2.html>