

NACHI 30332参数

| | | | | |
|--------|--------------|--------|-------|------|
| 外形尺寸 | d | 160 | mm | 内径 |
| | D | 340 | mm | 外径 |
| | B | 68 | mm | 宽度 |
| | T | 75 | mm | 宽度 |
| | C | 58 | mm | 宽度 |
| | r | 5~6.5 | mm | 径向 |
| | r | 5~8 | mm | 径向 |
| | 载荷中心 | a | 11.5 | mm |
| 安装尺寸 | da(min) | 182 | mm | (最小) |
| | db(max) | 205 | mm | (最大) |
| | Da(min) | 289 | mm | (最小) |
| | Db(min) | 310 | mm | (最小) |
| | S1(min) | 12 | mm | (最小) |
| | S2(min) | 17 | mm | (最小) |
| | Cone ra(max) | 4 | mm | 内圈 |
| | Cup ra(max) | 3 | mm | 外圈 |
| 重量 | Mass | 28700 | g | 重量 |
| 基本额定载荷 | Cr | 793000 | N | 动载荷 |
| | Cor | 981000 | N | 静载荷 |
| 极限速度 | Grease | 1100 | r/min | 脂润滑 |
| | Oil | 1400 | r/min | 油润滑 |

NACHI 30332图片

参考资料:<http://www.sozhou.com/p/99c74ec5.html>

