

FAG 23292-K-MB + AHX3292G参数

尺寸	D	830	mm	-
	B	296	mm	-
	a	11	mm	-
	b	50	mm	-
	D ₁	701.6	mm	-
	D _{a max}	798	mm	-
	d	460	mm	-
	d _{2G}	Tr480x5		-
	d _{a min}	492	mm	-
	d _s	12.5	mm	-
	l	349	mm	-
	n _s	23.5	mm	-
	r _{a max}	6	mm	-
	r _{min}	7.5	mm	-
说明		AHX3292G		型号, 退卸套
重量	m	699000	g	质量
	m ₁	65600	g	质量, 退卸套
基本额定载荷	C _r	7800000	N	基本额定动载荷, 径向
计算系数	e	0.37		-
	Y ₁	1.8		-
	Y ₂	2.69		-
基本额定载荷	C _{0r}	15000000	N	基本额定静载荷, 径向
计算系数	Y ₀	1.76		-
极限转速	n _G	680	r/min	极限转速
尺寸	d _{1H}	440	mm	-
参考转速	n _B	295	r/min	参考速度
疲劳极限载荷	C _{ur}	620000	N	疲劳极限载荷, 径向

FAG 23292-K-MB + AHX3292G图片



参考资料:<http://www.sozhou.com/p/9ae7a4f9.html>