

FAG 241/600-B-K30-MB + AH241/600参数

极限转速	n_G	480	r/min	极限转速
参考转速	n_B	149	r/min	参考速度
疲劳极限载荷	C_{ur}	1780000	N	疲劳极限载荷, 径向
尺寸	d_{1H}	570	mm	-
	D	980	mm	-
	B	375	mm	-
	a	30	mm	-
	b	50	mm	-
	D_1	833	mm	-
	$D_{a \max}$	948	mm	-
	d	600	mm	-
	d_{2G}	Tr625x6		-
	$d_{a \min}$	632	mm	-
	d_s	12.5	mm	-
	l	425	mm	-
	n_s	23.5	mm	-
	$r_{a \max}$	6	mm	-
	r_{\min}	7.5	mm	-
	说明		AH241/600	
重量	m	1170000	g	质量
	m_1	118000	g	质量, 退卸套
基本额定载荷	C_r	11600000	N	基本额定动载荷, 径向
计算系数	e	0.38		-
	Y_1	1.79		-
	Y_2	2.67		-
基本额定载荷	C_{0r}	26000000	N	基本额定静载荷, 径向
计算系数	Y_0	1.75		-

FAG 241/600-B-K30-MB + AH241/600图片



参考资料:<http://www.sozhou.com/p/9ef41756.html>